

# W400LVe

Bright projection



- **Bright WXGA projector – 4000 ANSI lumens**
- **Easy connectivity – HDMI, VGA, USB power**
- **Clear, powerful audio - 10W speaker**
- **Lightweight and portable**



Project bright and vibrant presentations effortlessly any time of day in HD. Designed for meeting rooms and classrooms, the W400LVe boasts amazing colour, long lamp life and energy-saving features for a lower overall cost of ownership.

This projector is easy to connect to with multiple inputs, a built-in speaker and USB Power. Perfect for connecting HDMI dongles such as Google Chromecast or a laptop, PC or Blu-ray player for clear projected images with sound. Portable and lightweight projector can be installed or taken on the move for off-site meetings with the optional carry bag (sold separately).

## Specifications

EAN: 5055387664791, Colour: Black

### Display/imagen

Tecnología de visualización	DLP™
Resolución	WXGA (1280x800)
Brillo	4,000 lumens
Ratio de contraste	25,000:1
Relación de aspecto nativo	16:10
Ratio de aspecto - compatible	4:3, 16:9
Corrección Keystone- Vertical	+/-40°
Frecuencia de muestreo horizontal	15.38 ~ 91.15Khz
Frecuencia de muestreo vertical	50 ~ 85(120 for 3D)Hz
Uniformidad	75%
Tamaño de pantalla	32.24" ~ 299.53" diagonal

### Info Lámpara

Fuente de luz	Lámpara
Vatios lámpara	203
Vida de lámpara (horas)	6000 (Brillante), 12000 (Dinámica), 10000 (Eco), 15000 (Eco+)

### Óptica

Distancia de tiro	1.55:1 ~ 1.73:1
Distancia de proyección (m)	39.37" - 472.44"
Zoom	1.1
Tipo de zoom	Manual
Distancia focal (mm)	21.85 mm~24mm/0.86"~0.945"
Offset nativo	112%

### Conectividad

Conexiones	<b>Entradas</b> 1 x HDMI 1.4a / 3D , 1 x VGA (YPbPr/RGB), 1 x Video compuesto, 1 x Audio 3.5mm <b>Salidas</b> 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A <b>Control</b> 1 x RS232
------------	---

### General

Nivel sonoro (tipico)	27dB
Nivel sonoro (max)	29dB
Compatibilidad PC	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
Compatibilidad 2D	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
Compatibilidad 3D	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Seguridad	Barra de seguridad, Kensington Lock, Interfaz protegida por contraseña
idiomas OSD / display	25 idiomas: Árabe, Checo, Danés, Holandés, Inglés, Farsi, Finlandés, Francés, Alemán, Griego, Húngaro, Indonesio, Italiano, Japonés, Noruego, Polaco, Portugués, Rumano, Ruso, Chino (simplificado), Español, Sueco, Chino (tradicional), Turco, Vietnamita
Condiciones de funcionamiento	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Control remoto	Mando tipo tarjeta extraplano
Altavoces	1
Wattios por altavoz	10W
Contenido de la caja	AC power cord Remote control Battery Basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit, WHD200

### Corriente

Fuente de alimentación	100 ~ 240V, 50 ~ 60Hz
Consumo energético (standby)	0.5W
Consumo energético ( min.)	187W
Consumo energético ( máx.)	225W

### Peso y dimensiones

Dimensiones (W x D x H)	12.44" x 9.61" x 4.25"
Gross weight	7.89 lbs
Net weight	6.7 lbs

