

ViewSonic® PROJECTOR

Pro10100

Key Features



Product Description

The ViewSonic Pro10100 is a high-brightness XGA (hi-resolution 4:3) installation projector boasting 6,000 ANSI Lumens of brightness and is designed for theaters, museums, auditoriums, lecture halls and other large commercial venues. Pro10100 product features include motorized zoom, motorized focus & lens-shift, network management, DICOM SIM mode, setting memory, 360-degree installation and 24/7 continuous use. Optional features include interchangeable lenses, image-correction technology for 4-corner, curve, pincushion and barrel & rotation projection surfaces, and multiple-image edge-blending capability.

Visit Us www.viewsonic.com

COMPATIBILITY

PC:	VGA to WSXGA+ (1680x1050)
Mac®:	Up to 1152x870

DIMENSIONS

Physical (WxHxD):	452.8x379.1x205.5 (mm)
-------------------	------------------------

PACKAGE CONTENTS

3m Power Cords x1, 1.8m VGA Cable x 1, Remote Control with battery (AA x 2) x1, ViewSonic Wizard DVD x 1, Quick Start Guide x1

INPUT SIGNAL

Frequency:	Horizontal: 15~100 kHz
	Vertical: 48~100 Hz
Computer and Video:	NTSC M (3.58 MHz), 4.43MHz
	PAL (B, D, G, H, I, M, N,60)
	SECAM (B, D, G, K, K1, L)
Computer and Video:	SD 480i and 576i
	ED 480p and 576p
	HD 720p (50/60Hz) , 1080i (50/60Hz), 1080p(24/25/30/50/60Hz)

CONNECTOR

Audio Out:	3.5mm Mini-stereo Jack x 1
HDMI (input):	x 1 (HDMI 1.3)
Audio Input:	3.5mm Mini-stereo Jack x 1
S-Video:	Mini-Din 4 pin x 1
Component:	BNC(RGBHV, Y/Pb/Pr, Y/Cb/Cr) x 1
Composite Input:	RCA Type x 1
RGB Input:	x 1
RGB Output:	x 1

POWER

Voltage:	100~240Vac 50/60Hz
Consumption:	515W (max)

CONTROLS

RS232:	x 1
--------	-----

DISPLAY

Contrast Ratio:	4,400:1 (DCR)
Aspect Ratio:	4 : 3
Throw Distance:	LEN-008: 1.01 – 7.68m
	LEN-009: 1.28 – 9.63m
	LEN-010: 1.61 – 18.29m
Throw Ratio:	LEN-008: 0.99 – 1.26:1
	LEN-009: 1.26 – 1.58:1
	LEN-010: 1.58 – 3.00:1
Brightness:	6000 ANSI Lumens
Lamp life (Normal / Eco / Dynamic Eco):	1500 / 2000
Resolution:	XGA 1024(H) x 768(D)
Keystone:	+20°~-20° Digital Vertical Keystone Correction
Size:	50"~300" Diagonal
Lens:	Sold separately LEN-008: 1.28x
	LEN-009: 1.25x
	LEN-010: 1.9x

LANGUAGE

English, German, French, Spanish, Italian, Russian, Traditional Chinese, Simplified Chinese, Japanese, Korean, Swedish, Turkish, Portuguese, Polish, Norwegian

AUDIO

Speakers:	10W
-----------	-----

WEIGHT

Net:	16 (Kg)
------	---------

OPERATING CONDITIONS

Humidity:	10%~90% Non-Condensation
Temperature:	41°~104°F (5°~40°C)

PORT

RJ45:	x 1
-------	-----