

ViewSonic® PROJECTOR **PX706HD**

Key Features

- Short throw projection
- 1.2X optical zoom
- USB Type-C input
- 3X fast input
- Gaming Mode



Product Description

The ViewSonic PX706HD is projector design for big screen gaming at home with a brightness of 3,000 ANSI Lumens, 1080p resolution, short throw lens and 1.2x adjustable zoom for flexible installation and the versatility to play games in any room in your house. The projector comes equipped with 3X Fast Input for more responsive gaming control via low input lag along with specialized game modes for clear image detail in dark scenes. Whether playing racing games, shooting games, or any other type of game, PX706HD optimizes screen performance and offers big screen visuals to take the excitement to the next level and makes multiplayer gaming more enjoyable. PX706HD has been designed with a Powerful audio provided by the projector's built-in 5W cube speakers along with SonicExpert and SonicMode enhancement deliver an immersive multisensory gaming experience.

Visit Us www.viewsonic.com

SPECIFICATION

| | |
|------------------------------------|--|
| Projection System: | 0.65" 1080p |
| Native Resolution: | 1920x1080 |
| DC Type: | DC3 |
| Brightness: | 3000 |
| Contrast Ratio with SuperEco Mode: | 22000:1 |
| Display Color: | 1.07 Billion Colors |
| Light Source: | Lamp |
| Light Source Life (Nor/SuperEco): | 4000/15000 |
| Lamp Watt: | 240W |
| Lens: | F=2.6-2.78f= 10.2~12.24 |
| Projection Offset: | 105%+/-5% |
| Throw Ratio: | 0.69-0.83 |
| Image Size: | 60"~120" |
| Throw Distance: | 0.9m-2.2m (100"@1.5m) |
| Keystone: | +/- 20° (Vertical) |
| Optical Zoom: | 1.2x |
| Audible Noise (Eco): | 27dB |
| Response Time: | 16ms |
| Resolution Support: | VGA(640 x 480) to FullHD(1920 x 1080) |
| HDTV Compatibility: | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p |
| Video Compatibility: | NTSC, PAL, SECAM |
| Horizontal Frequency: | 15K~102KHz |
| Vertical Scan Rate: | 23~120Hz |

INPUT

| | |
|-------------------------------------|------------------------|
| Computer in (share with component): | 1 |
| Composite: | 1 |
| Audio-in (3.5mm): | 1 |
| HDMI (HDCP): | 2 (HDMI 1.4/ HDCP 1.4) |
| USB Type C: | 1 (5V/ 2A) |

OUTPUT

| | |
|--------------------|---------|
| Audio out (3.5mm): | 1 |
| Speaker: | 5W Cube |

CONTROL

| | |
|-----------------------------|---|
| RS232: | 1 |
| USB Type Mini B (Services): | 1 |

OTHERS

| | |
|--|-----------------------------|
| Power Supply Voltage: | 100-240V+/- 10%, 50/60Hz AC |
| Power Consumption: | Normal: 310W Standby: <0.5W |
| Operating Temperature: | 0~40°C |
| Net Weight: | 2.7kg |
| Dimensions (WxDxH) with Adjustment Foot: | 293x115x220 mm |

| | |
|-----------|--|
| Language: | English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese |
|-----------|--|

STANDARD ACCESSORY

| | |
|-----------------|---|
| Power Cord: | 1 |
| Remote Control: | 1 |
| QSG: | 1 |
| Lens Cover: | 1 |
| USB Type C: | 1 |

OPTIONAL ACCESSORY

| | |
|--------------------|---------|
| Lamp/Light Source: | RLC-118 |
|--------------------|---------|